



Chemical protection

BUTOFLEX 651

short wear



CHEMICAL PROTECTION
TYPE A

EN388



0010X

EN ISO 374-1



TYPE A
ABCILMNOS

EN ISO 374-5



EN 16350



CATEGORY 3



0334

DEXTERITY

EN ISO 21420:
5/5

Ultimate specific chemical resistance

(SPECIFIC ADVANTAGES)



Protection of electronic device from ElectroStatic Discharge (ESD)

- In compliance with the requirement of the norm EN 16350, standard for protective gloves - Electrostatic properties : <1,0 10E5



Comfort

- Unrivalled flexibility and dexterity



Skin protection

- Ultimate specific chemical resistance, for very corrosive acids, ketones, esters and amine derivatives



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

(INDUSTRIES)

- Mechanical industry
- Chemical industry
- Cosmetics and Pharmaceutical industry

(APPLICATIONS)

- Metal treatment and degreasing
- Formulating paints, varnishes, resins and inks
- Handling and repackaging chemicals
- Sampling chemicals
- Handling in laboratories



Chemical protection

BUTOFLEX 651

short wear

LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
0 0 1 0 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance

EN ISO 374-1	CHEMICAL RISKS
	A: Methanol
TYPE A	B: Acetone
	C: Acetonitrile
	I: Ethyl acetate
	L: Sulphuric acid 96%
	M: Nitric acid 65%
	N: Acetic acid 99%
	O: Ammonia 25%
	S: Hydrofluoric acid 40%

EN 16350	PROTECTION AGAINST STATIC ELECTRICITY
----------	---------------------------------------



EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Smooth
Exterior finish	Embossed texture
Material	Butyl
Cuff characteristic	Rolled Cuff
Colour.s	Black
Length (cm)	37
Thickness (mm)	.56
European sizes	7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	< 1E+05 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.15 E+05 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/carton
-----------	------------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/2132
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France