USER INSTRUCTIONS

Applicable to products: AG2 series

Economic Operator	Role	Identifier	Address	Post Code	Country
R. Glover Ascroft	Manufacturer	EORI GB220731409000	Enfield	EN3 6AW	UK
SATRA Technology Centre	UKCA Type examination and certification	Approved Body 0321	Kettering	NN16 8SD	UK
SATRA Technology Europe	CE Type examination and certification	Notified Body 2777	Dublin	D15 YN2P	EI

This product group is classed as Personal Protective Equipment (PPE) by the European Regulation (EU) 2016/425 and under UK law as amended. It has been shown to comply with EU and UK law through appropriate testing to EU Harmonised European Standards and UK Designated Standards. The product group has been assessed to: EN ISO 21420:2020, EN388:2016+A1 2018 and EN407:2020 to the Intermediate Design standard (Category 2).

CAREFULLY READ THESE INSTRUCTIONS BEFORE USING THIS PRODUCT

THE PRODUCT – These protective gloves are intended for use in workplace environments where heat is a factor. The product provides contact heat protection when handling hot solid objects to 150°C for a maximum of 15 seconds. In addition the product will provide good cut resistance and tearing resistance. The product will offer homogeneous protection over its entire length.

No PPE item provides full protection and care must always be taken while carrying out the risk related activity.

PERFORMANCE AND LIMITATIONS TO USE - When tested in accordance with the requirements of EN388:2016+A1 2018 and EN407:2020, the product achieved the following performance levels, before and after laundering to EN ISO 6330:2012:

EN388:2016+A1 2018 - Mechanical Hazards



Abrasion resistance	level 0*	(0-4)
Circular blade cut resistance	level X	(0-5)
Tear resistance	level 4	(0-4)
Puncture resistance	level X	(Not tested)
TDM cut resistance	level B	(A-F)

XIXXXX

EN40/:2020 - Thermal Risks		
Limited Flame Spread	X	(Not tested)
Contact heat	1	(0-4)
Convective heat	X	(Not tested)
Radiant heat	X	(Not tested)
Small molten metal splash	X	(Not tested)
Large molten metal splash	X	(Not tested)

^{* 0} indicates that the glove falls below the minimum performance level for the given individual hazard.

ADVISORIES FOR EN388:2016 MECHANICAL RISKS

Due to the tear resistance result, ideally these gloves should not be worn in environments where there is the risk of entanglement by moving parts of machines.

FITTING AND SIZING – Ensure a suitable hand size is selected when donning / doffing the product. This product is seamless in design therefore no further adjustment is necessary. This product is ambidextrous and may be worn for use on either hand. Gloves are available in sizes 7. 8.9 and 10.

COMPATIBILITY - To optimise protection, in some instances it may be necessary to use these products with suitable boots/headwear or workwear. In this case, before carrying out the risk related activity, consult your supplier to ensure that all your protective products are compatible and suitable for your application.

ADVISORIES FOR EN407:2020 THERMAL RISKS

Do not use this product in the presence of naked flame. Due to the glove's knitted construction, do not use as the sole means of protection where there is the potential for contact with hot liquids: also use a suitable liquid-proof over-glove.


STORAGE AND OBSOLESCENCE - When stored in dry conditions in its original packaging, the product will not suffer from any changes in physical properties for up to 5 years from date of manufacture. Keep the product away from direct sun to avoid colour fade.

IN USE - If the product becomes worn or damaged it will **NOT** provide the declared protection, and it should be immediately replaced without further use. Do not reverse (turn inside out) the product for use as PPE. Do not use the product in any way other than as hand/arm protection. To preserve hand hygiene, communal use is not recommended.

MAINTENANCE AND CLEANING - The product will not require any additional maintenance during its working life. Check the product's surface for any signs of wear, damage or soling before commencing use. This product may be laundered up to 26 times in accordance with the cleaning programme indicated on the product label. It is the end user's responsibility to monitor the number of remaining laundering cycles. The product must be discarded after use following the final laundering cycle. Do not dry clean. If the product becomes too worn, damaged or soiled, then it should be replaced.

The Declaration of Conformity for this product can be downloaded at www.r-glover-ascroft.com/product-range

MARKINGS - The product is marked with:



- 2. The CE and UKCA conformity marks, showing that the product meets the requirements of EU and UK PPE legislation.
- 3. The Product's reference number.
- 4. Pictograms indicating the product meets the requirements of EN388:2016+A1 2018 and EN407:2020
- 5. The Company's Website URL

